

Multiple Function Time Attendant System And Door Access Control POWER S



- Professional appearance design with excellent workmanship and easy installation.
- Multi colour LCD, TFT HD screen in 3.5 inch
(Able to display characteristic picture and colour photos)
- Multiple identification modes: FP, IC card, password and camera photograph.
- Various networking communication protocol: RJ45 Ethernet, USB disk etc.
- Offline function available for distance: USB disk to upload/download files.
- Real time transfer on reliable attendance data based on steady network platform.
- Multiple languages available: Chinese simplified, Chinese traditional, English etc.
- Auxiliary functions:
 - ✓ Memo or Notice play
 - ✓ birthday reminder
 - ✓ Advertisement, etc.
- Storage capacity: dynamic allocation and expansion.
- Enabled by advanced Linux embedded operation system and ARM9 hardware platform,
- Device can work around the clock with steady and reliable performance.
- Wiegand interface available to connect an external Wiegand 26/34 card reader.
- Fast recognition with the most advanced fingerprint sense technology algorithm, 0.000001 at error rate.

Parameter:

Identification Mode	FP / IC card / password / camera photograph
Identification Speed	RF card identification < 0.2s
FAR / FRR	< 0.0001 % / < 0.01 %
Storage Capacity	60MB Flash Disk, dynamic allocation and extension according to staff number
Display	3.5 inches color TFT LCD resolution 320x240
Network Interface	10/100 Base-T Ethernet interface
Communication Protocol	TCP/IP, RS232, USB FLASH DISK, SD Card
Photography	1.30 mega pixels, HD color camera
USB Interface	Internal USB2.0 Hi-speed interface
Notice Announcement	Remote-control announcement
USB Transfer	U disk to store, upload and download staff archives
Sound Effect	Voice Reminder, Hour Striking
Multimedia Function	Advertising and mpg file play
Power	DC 12V, 2A
Working Environment	Temperature 0-50°C / Humidity 10%-90%
Dimension	173x131x45 (mm)

